

PETRONAS AGRILUB UNIVERSAL 15W-40

Premium Quality Super Tractor Oil Universal (STOU) Meeting API CE/SF and API GL-4.

Petronas Agrilub Universal is an SAE 15W-40 premium quality multipurpose oil specially formulated to satisfy various lubrication requirements of diesel and gasoline engines, transmissions, hydraulics, final drives and wet brakes and clutches of most modern farming equipment.

Formulated using premium quality mineral oils and advanced additives systems to provide excellent engine cleanliness, superior wear protection, excellent resistance to oxidation and deposit formation and ensuring chatter-free performance for the wet brake system.

Applications

Recommended for the lubrication of engines (both naturally aspirated and turbocharged), transmissions, final drives, hydraulic and wet brakes systems of the full range tractors and other farming equipment.

Customer Benefits

- One oil to satisfy all the oil-lubricated tractor components
- Excellent piston deposits control and maintain excellent engine cleanliness
- Outstanding thermal stability and oxidation resistance at high operating temperature.
- Effective load carrying capability in transmissions, gears and bearings to prolong component life and reliable performance
- Excellent friction characteristic to ensure chatter-free performance in wet brake system
- Good protection against rust and corrosion

Product Typicals

Characteristics	Value
Density @ 15 °C, kg/l	0.887
Pour Point, °C	-30.0
Flash Point, °C	222
Kinematic Viscosity, cSt	
@ 40 °C	103
@ 100 °C	14.0
Viscosity Index	137
Cold Cranking Visc.@ -15 °C, cP	3,000
ASTM Colour	5.0

Specifications

API CE/CD/SF
 API GL-4
 John Deere J27
 Massey Ferguson M-1139
 Ford M2C-159C
 MB 227.1
 Caterpillar TO-2
 Allison C-4

Customer Advice

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.