

Product Data Sheet

Effective Date 13.03.2015

Version 1.0



PETRONAS BRAKE & CLUTCH FLUID DOT 3

PETRONAS Brake & Clutch Fluid DOT 3 is a clear yellowish liquid specially formulated and tested for automotive hydraulic brakes and clutch control systems where DOT 3 fluid is recommended.

Applications

This PETRONAS Brake & Clutch fluid is recommended for use in all brake disc (including ABS), brake drum and hydraulic clutch system meeting the FMVSS 116 – DOT 3 performance level with the exception of certain Citroen and other vehicles requiring a mineral (LHM) fluid. It can be mixed safely with all brake & clutch fluid which meet this or the DOT 3 specifications.

All motor manufacturers recommend the brake & clutch fluid should be changed regularly within 1 – 2 years or after 20,000 – 40,000km. The changing frequency vary from model to model depend on manufacturers recommendation.

Precautions

- Use product from a completely sealed container only
- Brake fluid attacks paint work
- Keep out of reach of children
- If it get into the eyes or on the skin, flush with plenty of water
- If accidentally swallowed, induce vomiting and get medical attention immediately

Specifications, Approval and Recommendation

PETRONAS BRAKE & CLUTCH FLUID DOT 3 meets or exceeds the requirements of;

- FMVSS 116 – DOT 3
- ISO 4925
- JIS K2233
- SAE J1703
- MS 119

Typical Properties

Characteristics	Typical
Appearance	Clear Yellowish
Boiling Point (ERBP), min °C	205
Wet Boiling Point (ERBP), min °C	140
pH Value	8.6
Density @ 20°C, kg/l	1.03
Viscosity @ 100°C, cSt	1.95

* All technical data is provided for reference only.

Health, Safety and Environment

Product Data Sheet

Effective Date 13.03.2015

Version 1.0



PETRONAS BRAKE & CLUTCH FLUID DOT 3

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.